DIRECT DRIVE TRUCK - SINGLE TEMPERATURE



UNIT Width 789 mm x Depth 500 mm x Height 242 mm **CONDENSER** Width 789 mm x Depth 500 mm x Height 242 mm

V-100 MAX

Superior temperature control

The V-100, 200 and 300 series offer the optimal temperature control solution for trucks and vans up to 28m3. This complete range share many common components including the Direct Smart Reefer and has many modular options to fulfill the requirements of every customer with the following benefits:

- · Superior temperature control
- · User friendly Direct Smart Reefer
- Flexibility
- · Improved reliability of electrical components
- Ease of maintenance and service
- Ease of installation

PERFORMANCE				
REFRIGERATION CAPACITY SYSTEM NET COOLING CAPACITY UNDER A.T.P. COND	DITIONS AT 30 °C AMBIENT	AIRFLOW INDEPENDENT FROM UNIT ENGINE SPEED		
Capacity on engine power 0°C	2080 W	Volume @ 0 Pa static pressure	660 m³/hr	
Capacity on engine power -20°C	1090 W			
Capacity on electrical stand by 0°C	1260 W			
Capacity on electrical stand by -20°C	695 W			
HEATING CAPACITY				
On the road	1900 W			
Electric Stand By Operation	1100 W			

TECHNICAL DATA					
COMPRESSOR		GENERIC (BOXLENGTH, REFRIGERANT	Γ,)		
Model	QP08N	Box volume	8 - 16 m ³		
Displacement	82 cm ³	Refrigerant	R-404A		
Number of cylinders	6	Airflow	866 m³/hr		
		Controller	DSR III		
WEIGHT		DEFROST			
Installation kit	24 kg	Defrost	Automatic hot gas defrost		
Condenser w/o electric stand-by	25 kg				
Condenser with electric stand-by	43 kg				
Evaporator	9 kg				
Swash Plate Compressor	6.5 kg				
UNIT DIMENSIONS		ELECTRICAL STAND BY MOTOR			
Height	242 mm	Voltage / Phase / Frequency	230/1/50		
Width	789 mm	Rating	1.6 kW		
Depth	500 mm				
Condenser Height	242 mm				
Condenser Width	789 mm				
Condenser Depth	500 mm				
Evaporator Height	187 mm				
Evaporator Width	608 mm				

DIRECT DRIVE TRUCK - SINGLE TEMPERATURE

Evaporator Depth	490 mm
In-cab Controls Height	46 mm
In-cab Controls Width	135 mm
In-cab Controls Depth	25 mm

NOISE		REFRIGERANT	
Road Mode	84 dB(A)	Charge	10/30: 0.62 20: 0.85 50: 1.2 kg kg

DIRECT DRIVE TRUCK - SINGLE TEMPERATURE

	STANDARD FEATURE	OPTION / FACTORY FITTED	OPTION / DEALER FITTED
LIFE COST MANAGEMENT			
ThermoKare Service contracts			x
DATA CAPTURE & COMMUNICATIONS			
USB Datalogger			х
TouchPrint data logger			x
Wintrac (data analysis software)			x
Datalogger Jr			X
LOAD PROTECTION			
Hose extention 2 m/4 m/6 m		х	
Bumper feet roof mounting	x		
HMI holder	x		
Kit hoses large (upgrade)	x		
Kit swivel manifold (upgrade)	x		
Din Adapter		x	
Hose Cover		Х	
Muffler kit		x	
Snow Cover (kit deflector Small)		X	
Harness Extension 2m/4m/6m		X	
Door switches		х	