

## DIRECT DRIVE TRUCK - SINGLE TEMPERATURE



UNIT Width 1180 mm x Depth 485 mm x Height 222 mm

## V-200 MAX

### Superior temperature control

The V-100, 200 and 300 series offer the optimal temperature control solution for trucks and vans up to 28m<sup>3</sup>. This complete range share many common components including the Direct Smart Reefer and has many modular options to fulfill the requirements of every customer with the following benefits:

- Superior temperature control
- User friendly Direct Smart Reefer
- Flexibility
- Improved reliability of electrical components
- Ease of maintenance and service
- Ease of installation

#### PERFORMANCE

REFRIGERATION CAPACITY SYSTEM NET COOLING CAPACITY UNDER A.T.P. CONDITIONS AT 30 °C AMBIENT		AIRFLOW INDEPENDENT FROM UNIT ENGINE SPEED	
Capacity on engine power 0°C	2770 W	Volume @ 0 Pa static pressure	1241 m <sup>3</sup> /hr
Capacity on engine power -20°C	1460 W		
Capacity on electrical stand by 0°C	1970 W		
Capacity on electrical stand by -20°C	1130 W		
HEATING CAPACITY			
On the road	2800 W		
Electric Stand By Operation	2050 W		

#### TECHNICAL DATA

COMPRESSOR		GENERIC (BOXLENGTH, REFRIGERANT, ...)	
Model	QP13	Box volume	13 - 22 m <sup>3</sup>
Displacement	131 cm <sup>3</sup>	Refrigerant	R-404A/R-452A
Number of cylinders	6	Airflow	1100 m <sup>3</sup> /hr
		Controller	DSR III
WEIGHT		DEFROST	
Model 30	25 kg	Defrost	Automatic hot gas defrost
Model 50	75 kg		
Installation kit	24 kg		
Condenser w/o electric stand-by	25 kg		
Condenser with electric stand-by	43 kg		
Evaporator	15 kg		
Swash Plate Compressor	6.9 kg		
UNIT DIMENSIONS		ELECTRICAL STAND BY MOTOR	
Height	222 mm	Voltage / Phase / Frequency	230/1/50 -- 230/1/60 -- 400/3/50 -- 230/3/50 -- 230/3/60
Width	1180 mm	Rating	3.7 kW
Depth	485 mm		
Condenser w/o electric stand-by Height	242 mm		
Condenser w/o electric stand-by Width	789 mm		
Condenser w/o electric stand-by Depth	500 mm		

## DIRECT DRIVE TRUCK - SINGLE TEMPERATURE

Condenser with electric stand-by Height	221 mm
Condenser with electric stand-by Width	1180 mm
Condenser with electric stand-by Depth	485 mm
Evaporator Height	133 mm
Evaporator Width	985 mm
Evaporator Depth	525 mm
In-cab Controls Height	46 mm
In-cab Controls Width	135 mm
In-cab Controls Depth	25 mm

NOISE		REFRIGERANT	
Road Mode	85 dB(A)	Charge	10/30: 1.0 -- 20/50: 1.2 kg kg

## DIRECT DRIVE TRUCK - SINGLE TEMPERATURE

	STANDARD FEATURE	OPTION / FACTORY FITTED	OPTION / DEALER FITTED
<b>LIFE COST MANAGEMENT</b>			
ThermoKare Service contracts			x
<b>DATA CAPTURE &amp; COMMUNICATIONS</b>			
USB Datalogger			x
TouchPrint data logger			x
Wintrac (data analysis software)			x
Datalogger Jr			x
<b>LOAD PROTECTION</b>			
Hose extention 2 m/4 m/6 m		x	
Bumper feet roof mounting	x		
HMI holder	x		
Kit hoses large (upgrade)	x		
Kit swivel manifold (upgrade)	x		
Din Adapter		x	
Hose Cover		x	
Muffler kit		x	
Snow Cover (kit deflector Small)		x	
Harness Extension 2m/4m/6m		x	
Door switches		x	