DIRECT DRIVE TRUCK - SINGLE TEMPERATURE



UNIT Width 1180 mm x Depth 485 mm x Height 222 mm

V-300

Superior Temperature Control

The V-100, 200 and 300 series offer the optimal temperature control solution for trucks and vans up to 28m3. This complete range share many common components including the Direct Smart Reefer and has many modular options to fulfill the requirements of every customer with the following benefits:

- Modern compact platform
- User friendly Direct Smart Reefer
- Increased reliability
- $\cdot\,$ Easy maintenance, service and installation

PERFORMANCE						
REFRIGERATION CAPACITY SYSTEM NET COOLING CAPACITY UNDER A.T.P. CONDITIONS AT 30 °C AMBIENT		AIRFLOW INDEPENDENT FROM UNIT ENGINE SPEED				
Capacity on engine power 0°C	2965 W	Volume @ 0 Pa static pressure	2033 m³/hr			
Capacity on engine power -20°C	1260 W					
Capacity on electrical stand by 0°C	2090 W					
Capacity on electrical stand by -20°C	865 W					

	TECHNI	CAL DATA	
COMPRESSOR		GENERIC (BOXLENGTH, REFRIGERANT,)	
Model	QP15	Box volume	10 - 25 m ³
Displacement	146.7 cm ³	Refrigerant	R-134a
Number of cylinders	6	Airflow	1400 m ³ /hr
		Controller	DSR III
WEIGHT		DEFROST	
Model 30	25 kg	Defrost	Automatic hot gas defrost
Model 50	75 kg		
Installation kit	24 kg		
Condenser w/o electric stand-by	30 kg		
Condenser with electric stand-by	70 kg		
Evaporator	18 kg		
Swash Plate Compressor	6.8 kg		
UNIT DIMENSIONS		ELECTRICAL STAND BY MOTOR	
Height	222 mm	Voltage / Phase / Frequency	230/1/50 230/1/60 400/3/50 230/3/50 230/3/60
Width	1180 mm		
Depth	485 mm	Rating	3.7 kW
Condenser w/o electric stand-by Height	242 mm		5.7 10
Condenser w/o electric stand-by Width	789 mm		
Condenser w/o electric stand-by Depth	500 mm		
Condenser with electric stand-by Height	221 mm		
Condenser with electric stand-by Width	1180 mm		
Condenser with electric stand-by Depth	485 mm		
Evaporator Height	178 mm		
Evaporator Width	985 mm		
Evaporator Depth	551 mm		
In-cab Controls Height	46 mm		

DIRECT DRIVE TRUCK - SINGLE TEMPERATURE

In-cab Controls Width In-cab Controls Depth	135 mm 25 mm			
NOISE		REFRIGERANT		
Road Mode	85 dB(A)	Charge	10: 1.1 20: 1.3 kg	
AVAILABLE EVAP CONFIGURATIONS				

ES300

DIRECT DRIVE TRUCK - SINGLE TEMPERATURE

	STANDARD FEATURE	OPTION / FACTORY FITTED	OPTION / DEALER FITTED
LIFE COST MANAGEMENT			
ThermoKare Service contracts			x
DATA CAPTURE & COMMUNICATIONS			
USB Datalogger			x
TouchPrint data logger			x
Wintrac (data analysis software)			x
Datalogger Jr			X
LOAD PROTECTION			
Hose extention 2 m/4 m/6 m		x	
Bumper feet roof mounting	x		
HMI holder	×		
Kit hoses large (upgrade)	×		
Kit swivel manifold (upgrade)	x		
Din Adapter		x	
Hose Cover		x	
Muffler kit		х	
Snow Cover (kit deflector Small)		x	
Harness Extension 2m/4m/6m		x	
Door switches		x	